

P9 Pro Controller

P9 Pro will bring whole new experience to the users, excellent industrial protection, long standby time, and high work efficiency, which is suitable for hand-held operation. P9 Pro has faster running speed and operating efficiency, single 3400mAh smart battery can work continually for 10 hours, supports GPS/GLONASS/BDS, Single frequency B1 / L1 wave band.



3.7-inch display

3.7-inch second-generation display, resolution 480*640, transmissive type display, clearly visible under strong light, normal display at high and low temperatures.

OTG USB interface

The mini waterproof OTG USB interface is an abbreviation of On-the-Go USB, which is mainly used for connection of various devices or mobile devices with data exchange.

5 megapixel camera

Clearly capture live pictures.

Eighth generation ublox GNSS module

UBLox eighth generation GNSS module, support GPS / GLONASS / BDS, single frequency B1/L1.

Product Specification

Physical		Power Supply	
Operating System	Windows Mobile 6.5	Battery	7.2V
Processor	AM335X 1GHz		3400mAh
RAM	512MB DDR3		24.48Wh
Internal Storage	8G onboard flash (32G optional)	Working Time	10h
External Storage	Max to 32G, SD card	Environment	
Dimensions	192.0mm×93.5mm×43.0mm	Water/Dust proof	IP65
Weight	483g (without battery)	Operating Temperature	-30℃~+60℃
Camera	5-megapixels with autofocus	Storage Temperature	-40℃~+80℃
	VGA resolution ratio for video	Humidity	5%-95% non-condensing
Communication		Shock	1.2m(3.9 ft) free fall
Wi-Fi	802.11b/g/n WLAN		
Bluetooth	Bluetooth 2.1+EDR		
Network (PHS8-P)	Five Bands UMTS/HSPA+(WCDMA/FDD)		
	(850/800, 900, 1900 and 2100 MHz)		
	Quad-Band GSM		
	(850/900/1800/1900 MHz)		
Data Interface			
Screen	3.7inch Blaview TFT Transflective screen		
	480*640VGA resolution ratio		
Keyboard	Full alphanumeric		
	multi-function physical keyboard		



Shanghai e-Compass Science & Technology Co., Ltd
Lianhang Rd, Pujiang Town, Minhang District, Shanghai, China

Tel: +86 21 54467213
Email: info@esurvey-gnss.com
Web: www.esurvey-gnss.com
Edition: 20190403